

WM868-TI4



USAGE

The WM868-TI4 thermometer is designed to measure air temperature and radio transmission of measurement data.

UNIT DESCRIPTION

The thermometer is equipped with an integrated temperature sensor. Thanks to the side vents, rapid detection of ambient temperature changes is achieved.

The thermometer senses the temperature in minute intervals and transmits the current temperature at adjustable intervals, which is expressed as an average

of the measured values to a central data acquisition system via a communication gateway. Wireless data transmission is implemented in the 868 MHz radio band with a choice of one of three transmission technologies: wACO868, wM-BUS or LoRa. The thermometer uses two-way communication via the communication gateway for remote setting of basic parameters. Configuration parameters can be set using the configuration cable, or via Bluetooth from a computer, tablet, or mobile phone. The thermometer is powered by an internal 3.6 Ah battery. Thanks to this, the thermometer can operate for more than 5 years with a reporting period of 15 min. The thermometer is primarily designed for indoor environments, but it can also be used outdoors where the influence of splashing water is excluded.

TECHNICAL PARAMETERS

Wireless interface

• Frequency Band:

• Wireless Technology:

Protocols:

• Modulation:

868.0 - 868.6 MHz

WACO, wM-BUS, LoRa

WACO, wM-BUS

WACO GFSK, wM-BUS FSK, LoRa spread spectrum

Channel Width: WACO 100 kHz, 15 kHz, wM-BUS 200 kHz, LoRa 125 kHz

• Transmission Power: 10-25 mW

• Receiver Sensitivity: WACO -114 dBm, wM-BUS -105 dBm, LoRa -148 dBm

• Data Rate: WACO 2400, 38400 bps, wM-BUS 100 kbps, LoRa

250-11000 bps

• Output Impedance: 50 C

Antenna: external, SMA-female connector

Temperature measurement

• Measured temperature Range: -40 to 80 °C

• Temperature measure resolution: 0.1 °C

• Temperature measure accuracy: ± 0.2 °C (-10 \div 85 °C)

Bluetooth Specifications

Bluetooth Version: BLE 5.2
Bluetooth Frequency: 2.4 GHz
Bluetooth Data Rate: 1 Mbps
Bluetooth Maximum Power: 8 dBm

Power

Battery: Li-SOCI2
Battery Capacity: 3.6 Ah
Battery Life: 10 years

Physical Properties

Length: 70 mm
 Width: 70 mm
 Height: 27 mm
 Weight: 220 g

Operating Conditions

Operating Temperatures: (-20 to +50) °C
 Storage Temperatures: (0 to +40) °C

• Relative Humidity: 90% (non-condensing)

• IP Rating: IP20

UART configuration

• UART Data Rate: 9.6 kbps

• Transmission method: Asynchronous

• UART parameters: 8 data bits, 1 stop bit, no parity

• Voltage Level: 3.6 V (CMOS)